



GS 3/50 OPT W&D MFS

EXCLUSIVE FEATURES

- ▶ MODERN INDUSTRIAL DESING
- ▶ STRONG AND LIGHTWEIGHT TROLLEY WITH TOP MANUVRABILITY ON ANY TYPE OF FLOOR
- ▶ BIG RUBBER WHEELS WITH BREAKES
- ▶ DIMENSION COMPATIBLE WITH DOORS WIDTH
- ▶ 3 DOUBLE STAGE MOTORS WITH HIGHEST PERFORMANCE
- ▶ BEST SEALING OF THE POWERHEAD THANKS TO EXCLUSIVE BUILT-IN GASKET
- ▶ MODULAR CONFIGURATIONS TO COLLECT SOLID DIRECTLY IN THE TANK WITH A CYCLONIC CONVEYOR CONE, FINE DUST IN MICROFIBER BAG OF HIGH RESISTANCE OR LIQUID WITH A MECHANICAL STOP WHEN THE TANK IS FULL
- ▶ MANUAL FILTER SHAKER

GS 3/50 OPT W&D MFS

Code	ASD013653	
TECHNICAL DATA		
Usage	WET & DRY	
Number of phases	single phase	
Voltage / Frequency	V	220-240/50-60
N. and type of motor	3 x 2 stages	
Power	W	2900 - 3300 max
Water lift	mmH ₂ O	2300
Airflow	m ³ /h	600
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm ²	12.000 + 2.200
Sound Pressure Level	dB(A)	76
Dimensions (LxWxH)	mm	580x700x1150
Weight	Kg	68

STANDARD EQUIPMENT

CODE: FTDP88585
CLASS L STAR-SHAPED FILTER
12.000 cm²



CODE: FTDP00223
PCB PREFILTER WITH
CONDUCTIVE CARBON
FOILS



CODE: FTDP00553
HEPA H14 CARTRIDGE



CODE: -
CLASS M FLEECE BAG



CODE: PMVR06689
CONVEYOR CONE FOR
CYCLONIC EFFECT AND
FILTER PROTECTION



CODE: KTRI04157
FLOATING SYSTEM FOR
LIQUID RECOVERY



OPTIONAL ACCESSORIES

Class M Star shaped filter 12.000 cm ² resistant to 150°C	KTRI02483
Class M washable Cartridge	FTDP44260
Class M fleece bag -10 Pcs	KTRI05204
Mesh filter	FTDP28755
Fixing system for Mesh filter and cartridge	MPVR28723
Complete multipurpose premium tool kit 3 m ø38 mm	PMDT01227
Complete multipurpose premium tool kit 4 m ø50 mm	PMDT01228
Complete static dissipative tool kit 5 m ø50 mm	PMDT01192
Complete Oil&Abrasives Tool kit 4 m ø38 mm	PMDT00928
Anti-Static tool kit ø38-60 mm	PMDT00326

PLANET 1/50 OPT

EXCLUSIVE FEATURES

- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ MANUAL FILTER SHAKER
- ▶ BIG AND BRAKED WHEELS
- ▶ STARSHAPED FILTER, PCB PREFILTER AND ADDITIONAL CARTRIDGE
- ▶ TURBINE WITH PERFECT PERFORMANCE

PLANET 1/50 OPT

Code	ASID01200	
TECHNICAL DATA		
Usage	DRY	
Number of phases	single phase	
Voltage	V	230/50
N. and type of turbine	1xsingle stage	
Power	W	1500
Water lift	mmH ₂ O	1800
Airflow	m ³ /h	220
Tank Capacity	l	50
Diameter of inlet	mm	60
Filtering surface	cm ²	12.000
Sound Pressure Level	dB(A)	74
Dimensions (LxWxH)	mm	600x660x1600
Weight	Kg	65

STANDARD EQUIPMENT

CODE: FTDP88585
POLYESTER MAIN FILTER
12.000 cm²



CODE: FTDP00223
POLYCARBON PREFILTER



OPTIONAL ACCESSORIES

Basic tool kit ø38-60 mm	PMDT00325
Anti-Static tool kit ø38-60 mm	PMDT00326
Basic tool kit ø50-60 mm	PMDT00443
Anti-Static tool kit ø50-60 mm	PMDT00436