



SWEEPERS - RIDE ON

512 R

MAX PRODUCTIVITY

3500 m²/h

MAIN BRUSH PATH

500 mm

VOLTAGE SYSTEM

24 v



BATTERIES AND BATTERY CHARGER NOT INCLUDED

MOST FREQUENTLY USE

RETAIL



HORECA



CLEANING CONTRACTORS



MUNICIPALITIES



INNOVATIONS



SOFT
CLEANING
SURFACE



DBL™
DOUBLE
BATTERY
LIFE

SPECS



INTUITIVE CONTROL PANEL



FRONTAL WASTE TRAY



EASY MAINTENANCE

TECHNICAL DATA

		512 RET	512 RST
Code		MSUB00378	MSUB00380
PERFORMANCE			
Main brush cleaning path width	mm	500	500
Side brush cleaning path width	mm	700	700
Max theoretical productivity	m ² /h	3500	3500
Voltage	V-Ah	24	24
Installed power	W /HP	730	4 Hp
Hopper capacity	l	50	50
Hopper Discarghe System	Type/mm	Low-Manual	Low-Manual
Filtering surface	m ²	2,9	2,9
Fylter type		Panel -paper	Panel -paper
Max speed	km/h	5	5
Max Climb	%	2	2
Weight whitout batteries	kg	78	78
Dimension (LxWxH)	mm	1225x753x1182	1225x753x1182

STANDARD ACCESSORIES

		512 RET	512 RST
BRUSHES			
MAIN BRUSH		SPPV00051	SPPV00051
SIDE BRUSH		SPPV76057	SPPV76057
FILTERS			
FILTER		FTDP85298	FTDP85298

BATTERIES AND BATTERY CHARGERS

BATTERIES	N°	CHARACTERISTIC	DIMENSION	RUNNING TIME	BATTERY CHARGERS
IPC gel battery BAAC00105	2	12V 105 Ah (C5)	345x170x285	140	On board high frequency 24V 10 Ah KTRI01580 Stand alone high frequency BLS010 - BACA00133
EXIDE gel battery BAAC00024	2	12V 105 Ah (C5)	345x170x285	140	On board high frequency 24V 10 Ah KTRI01580 Stand alone high frequency BLS010 - BACA00133
Acid tubolar plate battery BAAC00070	2	12V 118 Ah (C5)	345x170x285	150	On board high frequency 24V 10 Ah KTRI01580 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12Ah -BACA00060
Acid flat plate battery BAAC00009	2	12V 105 Ah (C5)	345x170x285	140	On board high frequency 24V 10 Ah KTRI01580 Stand alone high frequency BLS010 - BACA00133 Stand alone low frequency 24V 12Ah -BACA00060

RECOMMENDED BATTERIES AND BATTERY CHARGERS